

Overview

HP ZBook Fury G1i 18 inch Mobile Workstation PC



Left

- |   |                                   |    |   |
|---|-----------------------------------|----|---|
| 1 | ACS & ALS Sensor                  | 9  | Security lock slot (Integrated)   |
| 2 | Microphone (2)                    | 10 | RJ45 Ethernet port (standard)   |
| 3 | IR Camera (optional)              | 11 | USB Type-A 5Gbps signaling rate (Powered)   |
| 4 | Webcam                            | 12 | Thunderbolt™ 4 with USB Type-C® 40Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)* |
| 5 | Camera Shutter                    | 13 | Headphone/mic combo jack  |
| 6 | IR LEDS (optional)                | 14 | Smart Card Reader   |
| 7 | Webcam LED                        | 15 | 3-button Touchpad   |
| 8 | Fingerprint reader / Power button |    |   |

\*Actual throughout may vary.



Overview



- 1

Power Indicator LED
- 2

Power connector
- 3

2 Thunderbolt™ 5 with USB Type-C® 80Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)\*
- 4

HDMI 2.1

Right

- 5

USB Type-A 5Gbps signaling rate
- 6

Headphone/mic combo jack
- 7

Smart Card Reader

\*Actual throughout may vary.



---

Features**PRODUCT NAME**HP ZBook Fury G1i 18 inch Mobile Workstation PC

---

**OPERATING SYSTEM****Preinstalled OS**

FreeDOS

Ubuntu Linux 24.04

Windows 11 Pro<sup>1</sup>Windows 11 Home - HP recommends Windows 11 Pro for business <sup>1</sup>Windows 11 Home Single Language - HP recommends Windows 11 Pro for business <sup>1</sup>Windows 11 Pro (Windows 11 Enterprise available with a Volume Licensing Agreement)<sup>1</sup>

<sup>1</sup> Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See <http://www.windows.com>.

**NOTE:** Your product does not support Windows 8 or Windows 7. In accordance with Microsoft's support policy, HP does not support the Windows<sup>®</sup> 8 or Windows 7 operating system on products configured with Intel<sup>®</sup> and AMD<sup>®</sup> 7th generation and forward processors or provide any Windows<sup>®</sup> 8 or Windows 7 drivers on <http://www.support.hp.com>. A full list of HP products and the Windows 10 versions tested is available on the HP support website. <https://support.hp.com/us-en/document/c05195282>

**PROCESSOR**

Intel<sup>®</sup> Core™ Ultra 9 Processor 285HX with Intel<sup>®</sup> Graphics and Intel<sup>®</sup> AI Boost (13 NPU TOPS), (2.1 GHz E-core base frequency, 2.8 GHz P-core base frequency, up to 4.6 GHz E-core Max Turbo frequency, up to 5.5 GHz P-core Max Turbo frequency, 36MB Cache, 8 P-cores and 16 E-cores, 24 threads), supports Intel vPro<sup>®</sup> Enterprise

Intel<sup>®</sup> Core™ Ultra 7 Processor 265HX with Intel<sup>®</sup> Graphics and Intel<sup>®</sup> AI Boost (13 NPU TOPS), (2.3 GHz E-core base frequency, 2.6 GHz P-core base frequency, up to 4.6 GHz E-core Max Turbo frequency, up to 5.3 GHz P-core Max Turbo frequency, 30MB Cache, 8 P-cores and 12 E-cores, 20 threads), supports Intel vPro<sup>®</sup> Enterprise

Intel<sup>®</sup> Core™ Ultra 7 Processor 255HX with Intel<sup>®</sup> Graphics and Intel<sup>®</sup> AI Boost (13 NPU TOPS), (1.8 GHz E-core base frequency, 2.4 GHz P-core base frequency, up to 4.5 GHz E-core Max Turbo frequency, up to 5.2 GHz P-core Max Turbo frequency, 30MB Cache, 8 P-cores and 12 E-cores, 20 threads)



### Features

- <sup>1</sup> Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. Intel's numbering, branding and/or naming is not a measurement of higher performance.
- <sup>2</sup> Intel Turbo Boost performance varies depending on hardware, software and overall system configuration. See <http://www.intel.com/technology/turboboost> for more information.
- <sup>3</sup> Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>
- <sup>4</sup> In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on <http://www.support.hp.com>.
- <sup>5</sup> Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.
- <sup>6</sup> Features and software that require a NPU may require software purchase, subscription or enablement by a software or platform provider, and third-party software may have specific configuration or compatibility requirements. Performance varies by use, configuration, and other factors.

### CHIPSET

Intel® WM890

### GRAPHICS

#### Integrated

Intel® Graphics

#### Discrete

NVIDIA RTX PRO 5000 Blackwell Generation Laptop GPU (24 GB GDDR7 dedicated);  
NVIDIA RTX PRO 4000 Blackwell Generation Laptop GPU (16 GB GDDR7 dedicated);  
NVIDIA RTX PRO 3000 Blackwell Generation Laptop GPU (12 GB GDDR7 dedicated);  
NVIDIA RTX PRO 2000 Blackwell Generation Laptop GPU (8 GB GDDR7 dedicated);  
NVIDIA RTX PRO 1000 Blackwell Generation Laptop GPU (8 GB GDDR7 dedicated);

#### Supports

RTX PRO 5000 / RTX PRO 4000 / RTX PRO 3000 Support Memory ECC  
DP 2.1, HDMI 2.1b  
Supports CUDA, Dynamic Boost



---

### Features

#### DISPLAY

##### Non-Touch

45.7 cm (18") diagonal, WQXGA (2560 x 1600), anti-glare, UWVA, LED, 500 nits, eDP 1.4 + PSR2, 165Hz, flat LCD Panel, 100% DCI-P3

##### Displays support

Supports up to 4 displays through the HP Thunderbolt 280W G4 Dock

##### Display Size

18.0"

45.7 cm (18")

---



---

### Features

#### STORAGE AND DRIVES

##### Primary M.2 Storage

4 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC  
2 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC  
2 TB PCIe® Gen4x4 NVMe™ SED SSD  
1 TB PCIe® Gen4x4 NVMe™ M.2 SSD TLC  
1 TB PCIe® Gen4x4 NVMe™ SED SSD  
512 GB PCIe® Gen4x4 NVMe™ M.2 SSD TLC  
512 GB PCIe® Gen4x4 NVMe™ SED SSD  
2 TB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD  
1 TB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD  
512GB Citadel PCIe-3x4 NVMe™ M.2 2280 TLC SED OPAL2 FIPS SSD

---



### Features

#### MEMORY

##### Maximum Memory

128 GB DDR5-5600 MT/s ECC;  
192 GB DDR5-5600 MT/s non-ECC  
256 GB DDR5-6400 MT/s non-ECC\*

##### Memory

16GB (1x16GB) DDR5 5600 SODIMM Memory  
32GB (1x32GB) DDR5 5600 SODIMM Memory  
32GB (2x16GB) DDR5 5600 SODIMM Memory  
64GB (2x32GB) DDR5 5600 SODIMM Memory  
64GB (4x16GB) DDR5 5600 SODIMM Memory  
128GB (4x32GB) DDR5 5600 SODIMM Memory  
192GB (3x64GB) DDR5 6400 CSODIMM Memory  
32GB (1x32GB) DDR5 5600 SODIMM ECC Memory  
32GB (2x16GB) DDR5 5600 SODIMM ECC Memory  
64GB (2x32GB) DDR5 5600 SODIMM ECC Memory  
128GB (4x32GB) DDR5 5600 SODIMM ECC Memory

##### Memory Slots

4 SODIMM  
2 DIMMs per channel; support up to 4000 MT/s  
DDR5 SODIMMS, system runs at 4000 MT/s  
Supports Dual Channel Memory

\*256 GB DDR5-6400 MT/s non-ECC will be available 2<sup>nd</sup> Half 2025

**NOTE:** Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.



### Features

#### NETWORKING /COMMUNICATIONS

##### WLAN

Intel® Wi-Fi 7 BE200 (2x2) and Bluetooth® 5.4 WLAN, vPro®<sup>1,2</sup>

Intel® Wi-Fi 7 BE200 (2x2) and Bluetooth® 5.4 WLAN, non-vPro®<sup>1,2</sup>

##### WWAN

HP R15 5G Solution WWAN<sup>3</sup>

##### WLPWAN

Qualcomm 9205 LTE-M (CAT-M1 fSVC)<sup>4</sup>

##### NFC

WNC XRAV-1 NFC

##### Ethernet

Intel I226-LM 2.5GbE Ethernet Controller

Intel I226-V 2.5GbE Ethernet Controller

<sup>1</sup>Wi-Fi 7: Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 7 (802.11BE) functionality requires compatible Windows 11 OS, compatible processor, and separately purchased Wi-Fi 7 router to support backwards compatibility with prior 802.11 specs. Available in countries where Wi-Fi 7 is supported. The specification for 802.11BE is a draft specification and is not final. If the final specification differs from the draft specification, it may affect the ability of the device to communicate with other 802.11BE devices.

<sup>2</sup>Intel vPro® requires Windows 10 Pro 64 bit or higher, a vPro supported processor, vPro enabled chipset, vPro enabled wired LAN and/or Wi-Fi 6E WLAN and TPM 2.0. Some functionality requires additional 3rd party software in order to run. Features of vPro® Essentials and Enterprise vary. See <http://intel.com/vpro>

<sup>3</sup>5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

<sup>4</sup>LPWAN (also called Mobile Narrowband) support HP Protect & Trace with Wolf Connect service through the subscription term, but do not support mobile broadband use.





---

### Features

#### AUDIO/MULTIMEDIA

##### Audio

Audio by Poly Studio,  
4 integrated stereo speakers; discrete amplifiers  
2 integrated dual array digital microphones

##### Speaker Power

(1W/8 ohm per speaker),

##### Camera

5MP Camera; IR Camera (optional)

---



### Features

#### KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

##### Keyboard

HP Premium Quiet Keyboard – spill-resistant, full-size, backlit keyboard and DuraKeys

HP Lumen RGB Z Keyboard – Full-size, per-key RGB backlit keyboard

##### Pointing Device

Clickpad with multi-touch gesture support, taps enabled as default

##### Function Keys

ESC: system information

F1 - Display Switching

F2 - Night Mode / Sure View LED: On = White; Off = Not illuminated

F3 - Brightness Down

F4 - Brightness Up

F5 - Audio Mute LED: On = Amber; Off = not illuminated

F6 - Volume Down

F7 - Volume Up

F8 - Mic Mute On = Amber; Off = not illuminated

F9 - Keyboard Backlight

F10 - Insert

F11 - Airplane Mode

F12 - Command center

> Print Screen

> Power On/Off On = White; Off = not illuminated

> Delete

> Fn key lock

> Microsoft Copilot<sup>1</sup>

##### Hidden Keys

home

end

Fn+R = Break

Fn+S = Sys Rq

Fn+C = Scroll Lock

Fn+W = Pause

<sup>1</sup>Copilot in Windows requires Windows 11. Some features require an NPU. Timing of feature delivery and availability varies by market and device. Requires Microsoft account to log in. Where Microsoft in Windows is not available, the Copilot key will lead to the Bing search engine. Use of Recall requires customer authentication using Windows Hello Enhanced Sign in Security (ESS) which requires a fingerprint reader or facial recognition camera and may not be supported on all platforms. See <http://aka.ms/WindowsAIFeatures>



### Features

#### SOFTWARE AND SECURITY

##### Software

Buy Microsoft Office (Sold Separately)  
CoPilot in Windows with CoPilot Key <sup>1</sup>  
Edge Customization  
HP Connection Optimizer  
HP Hotkey Support  
HP Mac Address Manager  
HP Notifications  
HP PC Hardware Diagnostics UEFI  
HP PC Hardware Diagnostics Windows  
HP Privacy Settings  
HP Services Scan <sup>2</sup>  
HP Smart Support <sup>3</sup>  
HP Support Assistant <sup>4</sup>  
HSA Fusion for Commercial  
HSA Telemetry for Commercial  
myHP<sup>5</sup>  
Poly Camera Pro  
Poly Lens<sup>6</sup>

##### Manageability Features

HP Client Catalog (download) <sup>7</sup>  
HP Client Management Script Library (download) <sup>8</sup>  
HP Cloud Recovery <sup>9</sup>  
HP Connect for Microsoft Endpoint Manager<sup>10</sup>  
HP Driver Packs (download) <sup>11</sup>  
HP Image Assistant (download) <sup>12</sup>  
HP Manageability Integration Kit (download) <sup>13</sup>  
HP Power Manager with Battery Health Manager (download) <sup>14</sup>

##### Security Management

Secured-Core PC Enable<sup>15</sup>  
Windows Hello Enhanced Sign-In Security (ESS)  
HP Wolf Security for Business which includes: <sup>16</sup>  
HP Sure Admin <sup>17</sup>  
HP Sure Click <sup>18</sup>  
HP Sure Recover <sup>19</sup>  
HP Sure Run <sup>20</sup>  
HP Sure Sense <sup>21</sup>  
HP Sure Start <sup>22</sup>  
HP Tamper Lock<sup>23</sup>



### Features

#### BIOS

Absolute Persistence Module <sup>24</sup>

Audio Permanent Disable

BIOS Update via Network

HP BIOS Recovery

HP BIOSphere <sup>25</sup>

HP DriveLock & Automatic DriveLock

HP Fingerprint Sensor <sup>26</sup>

HP Secure Erase <sup>27</sup>

HP Wake on WLAN

1. Copilot key is available on select Windows 11 PCs. Where Microsoft Copilot is not available, the Copilot key will lead to the Bing search engine. Copilot key feature availability varies by market, see [aka.ms/keysupport](https://aka.ms/keysupport). Copilot is NOT available in China, Russia, Belarus, and embargoed regions Cuba, Iran, North Korea, Crimea.
2. HP Services Scan is preinstalled and/or provided thru Windows Update and checks for service entitlement on each hardware device and downloads the applicable software agent automatically. To disable this feature, please follow the instructions at <http://www.hpdaas.com/requirements>. The HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to the HP Insights agent is required. For full system requirements, please visit <http://www.hpdaas.com/requirements>. Not available in China.
3. HP Smart Support requires the HP Insights agent to be installed. For more information about how to enable or to download HP Smart Support, please visit <http://www.hp.com/smart-support>. HP Services Scan is preinstalled and/or provided thru Windows Update and will check entitlement on each hardware device to determine if an HP Insights agent-enabled service has been purchased, and will download applicable software automatically. HP Insights agent is a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access is required. For full system requirements or to disable this feature, please visit <https://www.hpdaas.com/requirements>.
4. HP Support Assistant is available on Windows. For more information, please visit [www.support.hp.com/help/hp-support-assistant](http://www.support.hp.com/help/hp-support-assistant).
5. MyHP requires Windows 10 or higher OS.
6. Poly Lens Desktop requires a Windows OS.
7. HP Client Catalog not preinstalled, however available for download at (<https://www.hp.com/us-en/solutions/client-management-solutions.html>)
8. HP Client Management Script Library (<https://www.hp.com/us-en/solutions/client-management-solutions.html#tab=manageability-tools>).
9. HP Cloud Recovery is available for Z by HP, HP Elite and Pro desktops and laptops PCs with Intel® or AMD processors and requires an open, network connection. **NOTE:** You must back up important files, data, photos, videos, etc. before use to avoid loss of data. Detail please refer to: <https://support.hp.com/us-en/computer>.
10. HP Connect for Microsoft Endpoint Manager is available from the Azure Market Place for HP Pro, Elite, Z and Point-of-Sale PCs managed with Microsoft Endpoint Manager. Subscription to Microsoft Endpoint Manager required and sold separately. Network connection required.
11. HP Driver Packs not preinstalled, however available for download at <http://www.hp.com/go/clientmanagement>.
12. HP Image Assistant not preinstalled, however available for download at (<https://ftp.ext.hp.com/pub/caps-softpaq/cmit/HPIA.html>),
13. HP Manageability Integration Kit not preinstalled, however available for download from <https://www.hp.com/us->



### Features

[en/solutions/client-management-solutions.html#tab=manageability-tools](https://support.hp.com/en/solutions/client-management-solutions.html#tab=manageability-tools).

14. HP Power Manager with Battery Health can be downloaded by entering your system information here: [https://support.hp.com/en/document/ish\\_4449597-3519507-16](https://support.hp.com/en/document/ish_4449597-3519507-16).

15. Secured-Core PC Enable requires an Intel® vPro®, AMD Ryzen™ Pro processor or Qualcomm® processor with SD850 or higher and requires 8 GB or more system memory. Secured-core PC is enabled from the factory.

16. HP Wolf Security for Business requires Windows 10 or 11 Pro or higher, includes various HP security features and is available on HP Pro, Elite, RPOS and Workstation products. See product details for included security features.

17. HP Sure Admin requires HP G8 or newer platforms, Windows 10 or higher, HP BIOS, HP Manageability Kit or KMS Service from <http://www.hp.com/go/clientmanagement> and HP Sure Admin Local Access Authenticator smartphone app from the Android or Apple store.

18. HP Sure Click requires Windows 10 and higher. See [https://bit.ly/2PrLT6A\\_SureClick](https://bit.ly/2PrLT6A_SureClick) for complete details.

19. HP Sure Recover is available on select HP PCs and requires Windows 10 or 11 and an open network connection. You must back up important files, data, photos, videos, etc. before using HP Sure Recover to avoid loss of data. HP Sure Recover Gen6 with Embedded Reimaging is an optional feature on select HP PCs which requires Windows 10 or 11 must be configured at purchase. You must back up important files, data, photos, videos, etc. before use to avoid loss of data.

20. HP Sure Run is available on select HP PCs and requires Windows 10 and higher.

21. HP Sure Sense requires Windows 10 and higher. See product specifications for availability. On units with WWAN shipping to China, HP Sure Sense is only available via Softpaq download.

22. HP Sure Start is available on select HP PCs and requires Windows 10 and higher.

23. HP Tamper Lock must be enabled by the customer or your administrator.

24. Absolute Persistence firmware module is shipped turned off and can only be activated with the purchase a license subscription and full activation of the software agent. License subscriptions can be purchased for terms ranging multiple years. -Service is limited, check with Absolute for availability outside the U.S. Certain conditions apply. For full details visit: <https://www.absolute.com/about/legal/agreements/absolute/>.

25. HP BIOSphere features may vary depending on the platform and configuration.

26. HP Fingerprint Reader is an optional feature that requires Windows 10 or 11 and must be configured at purchase.

27. HP Secure Erase implements the methods outlined in the National Institute of Standards and Technology Special Publication 800-88r "Clear" sanitation method. HP Secure Erase does not support platforms with Intel® Optane™.



---

### Features

#### POWER

##### Power Supply <sup>16</sup>

HP 200W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;  
HP 280W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;  
HP 330W Slim 4.5 mm PFC Right Angle Smart (3-pin) AC Power Adapter;  
Not Included AC Adapter

##### Battery

HP 99 Wh Long Life Polymer Fast Charge 8 cell Battery

##### Power Cord

C13 1.83m Paper Sticker Flange Premium CWP Black Straight Halogen Free Power Cord  
C13 1.83m Paper Sticker Flange Premium CWP Black Straight Power Cord  
Not Included Power Cord

##### Battery life

TBD

---



---

### Features

#### WEIGHT & DIMENSIONS

##### Weight<sup>1</sup>

Starting at 7.78 lb

(Weight varies by configuration and components.)

Starting at 3.52 kg;

(Weight varies by configuration and components.)

##### Product Dimensions (w x d x h)

15.88 x 11.41 x 1.10 in

(Dimensions vary by configuration)

40.3 x 28.9 x 2.7 cm

(Dimensions vary by configuration)

---



---

### Features

#### PORTS/SLOTS

##### Left Side

- 1 power connector
- 2 Thunderbolt™ 5 with USB Type-C® 80 Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)\*
- 1 HDMI 2.1
- SD 7.0 Media Card Reader

##### Right side:

- 1 Thunderbolt™ 4 with USB Type-C® 40 Gbps signaling rate (USB Power Delivery, DisplayPort™ 2.1)\*
- 1 USB Type-A 10Gbps signaling rate
- 1 headphone/microphone combo
- 1 RJ-45
- 1 nano security lock slot
- 1 smart card reader

##### Expansion Slots

- SD 7.0 Media Card Reader

\*Actual throughput may vary.

---





---

### Features

#### **SERVICE AND SUPPORT**

1-year warranty and 90 day software limited warranty options depending on country. HP Worldwide Limited Warranty for the battery is aligned with the warranty period of the HP Hardware Product. Refer to <http://www.hp.com/support/batterywarranty/> for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: <http://www.hp.com/go/cpc>.

#### **Certification and Compliance**

ENERGY STAR® certified

EPEAT® registered configurations available

Low halogen

#### **Sustainable Impact Specifications**

40% post-consumer recycled plastic

Bulk packaging available

External power supply 90% efficiency;

Molded paper pulp cushion inside box is 100% sustainably sourced and recyclable;

Outside box and corrugated cushions are 100% sustainably sourced and recyclable



## Technical Specifications – System Unit

## SYSTEM UNIT

## Stand-Alone Power Requirements (AC Power)

**Nominal Operating Voltage** 19.5V**Average Operating Power****Integrated graphics** CPU < 55W**Discrete Graphics** NVIDIA RTX PRO 5000 Blackwell 135W

NVIDIA RTX PRO 4000 Blackwell 135W

NVIDIA RTX PRO 3000 Blackwell 115W

NVIDIA RTX PRO 2000 Blackwell 60W

NVIDIA RTX PRO 1000 Blackwell 60W

**Max Operating Power** <330W**Temperature****Operating** 32° to 95° F (0° to 35° C), System performance may be reduced above 32°C (89.6°F).

No sustained direct exposure to sunlight.

**Non-operating** -4-140°F (-20 - 60°C)**Relative Humidity****Operating** 10% to 90%, non-condensing**Non-operating** 5% to 95%; 38.7C (101.6F) maximum wet bulb tempera-ture; non-condensing.**Shock****Operating** 40 G, 2 ms, half-sine**Non-operating** 240G, 2ms, half sine**Random Vibration****Operating** 0.079 ~ 1.043 grams**Non-operating** 3.5 grams**Altitude (unpressurized)****Operating** 3048m (10,000ft)**Non-operating** 12192m (40,000ft)

## Planned Industry Standard Certifications

**Regulatory Model Number** HSN-I64C-8**UL** Yes**CSA** Yes**FCC Compliance** Yes**ENERGY STAR®** Yes**EPEAT** Gold**ICES** Yes**Australia /** Yes**NZ A-Tick Compliance** Yes**CCC** Yes**Japan VCCI Compliance** Yes**KC** Yes**BSMI** Yes**CE Marking Compliance** Yes**BNCI or BELUS** No

Technical Specifications – System Unit

CIT	
EAC	Yes
SASO	Yes
SABS	Yes
UKRSERTCOMPUTER	



Technical Specifications – Displays

DISPLAYS

Actual brightness will be lower with touchscreen or HP Sure View.  
Availability may vary by country

18.0 in WQXGA (2560 x 1600)  
Anti-Glare UWVA LED DCI-P3  
100 500 eDP 1.4+PSR2  
165Hzflat LCD Panel

Outline Dimensions (W x H)	394.56 x 264.80 (max)
Active Area	387.76 x 242.35 (typ)
Weight	560 (max)
Diagonal Size	18
Thickness	3.32/3.5 (max)
Interface	eDP 1.4
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1200:1 (typ)
Refresh Rate	165Hz (typ)
Brightness	500 (typ)
Pixel Resolution - Format	2560 x 1600 (WQXGA)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	DCI P3 100%
Color Depth	8
Viewing Angle	UWVA 89/89/89/89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	4.18 (max)/4.97(max)

## Technical Specifications – Storage

## STORAGE

**SSD 512GB 2280 PCIe-4x4  
NVMe Three Layer Cell**

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	512GB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen4X4
<b>Sequential Read</b>	6400 MB/s $\pm$ 20%
<b>Sequential Write</b>	3500 MB/s $\pm$ 20%
<b>Logical Blocks</b>	1000215215
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

**SSD 1TB 2280 PCIe-4x4 NVMe  
Three Layer Cell**

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	1TB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen4X4
<b>Sequential Read</b>	6400 MB/s $\pm$ 20%
<b>Sequential Write</b>	5000 MB/s $\pm$ 20%
<b>Logical Blocks</b>	2000409264
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

**1TB PCIe-4x4 2280 NVME Self  
Encrypted OPAL2 Three Layer  
Cell Solid State Drive**

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	1TB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen4X4
<b>Sequential Read</b>	6400 MB/s $\pm$ 20%
<b>Sequential Write</b>	5000 MB/s $\pm$ 20%
<b>Logical Blocks</b>	2000409264
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

**1TB PCIe-5x4 2280 NVMe Solid  
State Drive**

### Technical Specifications – Storage

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	1TB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen5X4
<b>Sequential Read</b>	13000 MB/s ±20%
<b>Sequential Write</b>	9000 MB/s ±20%
<b>Logical Blocks</b>	
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

#### 2TB PCIe-4x4 2280 NVMe Three Layer Cell Solid State Drive

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	2TB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen4X4
<b>Sequential Read</b>	6400 MB/s ±20%
<b>Sequential Write</b>	5000 MB/s ±20%
<b>Logical Blocks</b>	4000797360
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

#### 2TB PCIe-4x4 2280 NVMe Self Encrypted OPAL2 Three Layer Cell Solid State Drive

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	2TB
<b>NAND Type</b>	TLC
<b>Weight</b>	10 g (0.02 lb)
<b>Interface</b>	PCIe NVMe Gen4X4
<b>Sequential Read</b>	6400 MB/s ±20%
<b>Sequential Write</b>	5000 MB/s ±20%
<b>Logical Blocks</b>	4000797360
<b>Features</b>	Pyrite 2.0; TRIM; L1.2

#### 2TB PCIe-5x4 2280 NVMe Solid State Drive

<b>Form Factor</b>	M.2 2280
<b>Capacity</b>	2TB
<b>NAND Type</b>	TLC



Technical Specifications – Storage

Weight	10 g (0.02 lb)
Interface	PCIe NVMe Gen5X4
Sequential Read	13500 MB/s ±20%
Sequential Write	10000 MB/s ±20%
Logical Blocks	
Features	Pyrite 2.0; TRIM; L1.2

4TB PCIe-4x4 2280 NVMe  
Three Layer Cell double-sided  
M.2 Solid State Drive

Form Factor	M.2 2280
Capacity	4TB
NAND Type	TLC
Weight	15 g
Interface	PCIe NVMe Gen4X4
Sequential Read	6400 MB/s ±20%
Sequential Write	5000 MB/s ±20%
Logical Blocks	8001573552
Features	Pyrite 2.0; TRIM; L1.2



## Technical Specifications – Networking

## NETWORKING / COMMUNICATION

Intel BE200 Wi-Fi 7 +BT 5.4  
M.2 320MHz PCIe World-wide  
WLAN vPro<sup>1</sup>

## Wireless LAN Standards

IEEE 802.11a  
IEEE 802.11b  
IEEE 802.11g  
IEEE 802.11n  
IEEE 802.11ac  
IEEE 802.11ax  
IEEE 802.11be  
IEEE 802.11d  
IEEE 802.11e  
IEEE 802.11h  
IEEE 802.11i  
IEEE 802.11k  
IEEE 802.11r  
IEEE 802.11v

Interoperability  
Frequency Band

Wi-Fi certified  
802.11b/g/n/ax/be  
2.402 – 2.482 GHz  
802.11a/n/ac/ax/be  
4.9 – 4.95 GHz (Japan)  
5.15 – 5.25 GHz  
5.25 – 5.35 GHz  
5.47 – 5.725 GHz  
5.825 – 5.850 GHz  
5.955 – 6.415 GHz  
6.435 – 6.515 GHz  
6.535 – 6.875 GHz  
6.895 – 7.115 GHz

## Data Rates

802.11b: 1, 2, 5.5, 11 Mbps  
802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  
802.11n: max 300Mbps  
802.11ac : 1733Mbps  
802.11ax : max 2.4Gbps  
802.11be : max 5.76Gbps

## Modulation

Direct Sequence Spread Spectrum  
OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM,  
4096QAM

Security<sup>3</sup>

IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only





### Technical Specifications – Networking

	<p>AES-CCMP: 128 bit in hardware</p> <p>802.1x authentication</p> <p>WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES.</p> <p>WPA2 certification</p> <p>WPA3 certification</p> <p>IEEE 802.11i</p> <p>WAPI</p>
<b>Network Architecture Models</b>	<p>Ad-hoc (Peer to Peer)</p> <p>Infrastructure (Access Point Required)</p>
<b>Roaming</b>	<p>IEEE 802.11 compliant roaming between access points</p>
<b>Output Power<sup>2</sup></b>	<p>802.11b, 1Mbps : +17dBm minimum</p> <p>802.11g, 6Mbps : +16dBm minimum</p> <p>802.11a, 6Mbps : +17dBm minimum</p> <p>802.11n, MCS7(HT20) : +14dBm minimum</p> <p>802.11n, MCS7(HT40) : +13.5dBm minimum</p> <p>802.11ac MCS9(VHT20) : 13.5dBm minimum</p> <p>802.11ac MCS9(VHT40) : +13.5dBm minimum</p> <p>802.11ac MCS9(VHT80) : +12.5dBm minimum</p> <p>802.11ac MCS9(VHT160) : +10.5dBm minimum</p> <p>802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum</p> <p>802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum</p> <p>802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum</p> <p>802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum</p> <p>802.11be MCS13(EHT20)(6GHz) : 11.5dBm</p> <p>802.11be MCS13(EHT40)(6GHz) : 7.5dBm</p> <p>802.11be MCS13(EHT80)(6GHz) : 7.5dBm</p> <p>802.11be MCS13(EHT160)(6GHz) : 6.5dBm</p> <p>802.11be MCS13(EHT320)(6GHz) : 4.5dBm</p>
<b>Power Consumption</b>	<p>Transmit mode 3.1 W</p> <p>Receive mode 1.8 W</p> <p>Idle mode (PSP) 180 mW (WLAN Associated)</p> <p>Idle mode 50 mW (WLAN unassociated)</p> <p>Connected Standby 10mW</p> <p>Radio disabled 8 mW</p>
<b>Power Management</b>	<p>ACPI and PCI Express compliant power management</p> <p>802.11 compliant power saving mode</p>
<b>Receiver Sensitivity<sup>3</sup></b>	<p>802.11b, 1Mbps : -93.5dBm maximum</p> <p>802.11b, 11Mbps : -85dBm maximum</p> <p>802.11a/g, 6Mbps : -90.5dBm maximum</p> <p>802.11a/g, 54Mbps : -72.5dBm maximum</p> <p>802.11n, MCS0(HT20) : -90dBm maximum</p> <p>802.11n, MCS7(HT20) : -71.5dBm maximum</p> <p>802.11n, MCS0(HT40) : -88.5dBm maximum</p>



### Technical Specifications – Networking

	802.11n, MCS7(HT40) : -68.5dBm maximum
	802.11ac, MCS9(VHT20) : -88.5dBm maximum
	802.11ac, MCS9(VHT40) : -65.5dBm maximum
	802.11ac, MCS9(VHT80) : -60.5dBm maximum
	802.11ac, MCS9(VHT160) : -58.5dBm maximum
	802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum
	802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum
	802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum
	802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum
	802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum
	802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum
	802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum
	802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum
<b>Antenna type</b>	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230 : 2.8g 2. Type 1216: 1.3g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating: 14° to 158° F (–10° to 70° C) Non-operating: –40° to 176° F (–40° to 80° C)
<b>Humidity</b>	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
<b>Altitude</b>	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED OFF – Radio ON
<b>Subtitle</b>	HP Integrated Module with Bluetooth
<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology
<b>Frequency Band</b>	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
<b>Number of Available Channels</b>	2402 to 2480 MHz Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)



### Technical Specifications – Networking

<b>Transmit Power</b>	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
<b>Power Consumption</b>	Peak (Tx): 330 mW  Peak (Rx): 230 mW  Selective Suspend: 17 mW
<b>Bluetooth Software Supported Link Topology</b>	1. Microsoft Windows Bluetooth Software 2. Linux/Chrome OS Bluetooth Software.
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Certifications</b>	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407
<b>Bluetooth Profiles Supported</b>	ETSI 300 328, ETSI 301 893, ETSI 303 687 BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising 2Mbps LE LE Long Range BT5.3 Host to Controller Encryption Key Control Enhancements Compliance to the latest Errata Section 12.3 of BT 5.3 specification



Technical Specifications – Networking

- 1.Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
- 2. Check latest software/driver release for updates on supported security features.
- 3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
- 4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Intel BE200 Wi-Fi 7 +BT 5.4  
M.2 320MHz PCIe World-wide  
WLAN non-vPro <sup>1</sup>

Wireless LAN Standards	IEEE 802.11a
	IEEE 802.11b
	IEEE 802.11g
	IEEE 802.11n
	IEEE 802.11ac
	IEEE 802.11ax
	IEEE 802.11be
	IEEE 802.11d
	IEEE 802.11e
	IEEE 802.11h
	IEEE 802.11i
	IEEE 802.11k
	IEEE 802.11r
	IEEE 802.11v
Interoperability Frequency Band	Wi-Fi certified
	802.11b/g/n/ax/be
	2.402 – 2.482 GHz
	802.11a/n/ac/ax/be
	4.9 – 4.95 GHz (Japan)
	5.15 – 5.25 GHz
	5.25 – 5.35 GHz
	5.47 – 5.725 GHz
	5.825 – 5.850 GHz
	5.955 – 6.415 GHz
Data Rates	6.435 – 6.515 GHz
	6.535 – 6.875 GHz
	6.895 – 7.115 GHz
	802.11b: 1, 2, 5.5, 11 Mbps
	802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
	802.11n: max 300Mbps

### Technical Specifications – Networking

	802.11ac : 1733Mbps 802.11ax : max 2.4Gbps 802.11be : max 5.76Gbps
<b>Modulation</b>	Direct Sequence Spread Spectrum OFDM, BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM, 4096QAM
<b>Security<sup>3</sup></b>	IEEE and WiFi compliant 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI
<b>Network Architecture Models</b>	Ad-hoc (Peer to Peer)
<b>Roaming</b>	Infrastructure (Access Point Required) IEEE 802.11 compliant roaming between access points
<b>Output Power<sup>2</sup></b>	802.11b, 1Mbps : +17dBm minimum 802.11g, 6Mbps : +16dBm minimum 802.11a, 6Mbps : +17dBm minimum 802.11n, MCS7(HT20) : +14dBm minimum 802.11n, MCS7(HT40) : +13.5dBm minimum 802.11ac MCS9(VHT20) : 13.5dBm minimum 802.11ac MCS9(VHT40) : +13.5dBm minimum 802.11ac MCS9(VHT80) : +12.5dBm minimum 802.11ac MCS9(VHT160) : +10.5dBm minimum 802.11ax MCS11(HE20)(6GHz) : +11.5dBm minimum 802.11ax MCS11(HE40)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE80)(6GHz) : +7.5dBm minimum 802.11ax MCS11(HE160)(6GHz) : +7.5dBm minimum 802.11be MCS13(EHT20)(6GHz) : 11.5dBm 802.11be MCS13(EHT40)(6GHz) : 7.5dBm 802.11be MCS13(EHT80)(6GHz) : 7.5dBm 802.11be MCS13(EHT160)(6GHz) : 6.5dBm 802.11be MCS13(EHT320)(6GHz) : 4.5dBm
<b>Power Consumption</b>	Transmit mode 3.1 W Receive mode 1.8 W Idle mode (PSP) 180 mW (WLAN Associated) Idle mode 50 mW (WLAN unassociated) Connected Standby 10mW Radio disabled 8 mW



### Technical Specifications – Networking

<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Receiver Sensitivity<sup>3</sup></b>	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -85dBm maximum 802.11a/g, 6Mbps : -90.5dBm maximum 802.11a/g, 54Mbps : -72.5dBm maximum 802.11n, MCS0(HT20) : -90dBm maximum 802.11n, MCS7(HT20) : -71.5dBm maximum 802.11n, MCS0(HT40) : -88.5dBm maximum 802.11n, MCS7(HT40) : -68.5dBm maximum 802.11ac, MCS9(VHT20) : -88.5dBm maximum 802.11ac, MCS9(VHT40) : -65.5dBm maximum 802.11ac, MCS9(VHT80) : -60.5dBm maximum 802.11ac, MCS9(VHT160) : -58.5dBm maximum 802.11ax, MCS11(HE20)(6GHz) : -59.5dBm maximum 802.11ax, MCS11(HE40)(6GHz) : -56.5dBm maximum 802.11ax, MCS11(HE80)(6GHz) : -53.5dBm maximum 802.11ax, MCS11(HE160)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT20)(6GHz) : -55.5dBm maximum 802.11be, MCS13(EHT40)(6GHz) : -53.5dBm maximum 802.11be, MCS13(EHT80)(6GHz) : -51.5dBm maximum 802.11be, MCS13(EHT160)(6GHz) : -48.5dBm maximum 802.11be, MCS13(EHT320)(6GHz) : -45.5dBm maximum
<b>Antenna type</b>	High efficiency antenna with spatial diversity Two embedded tri-band 2.4/5/6 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications
<b>Form Factor</b>	PCI-Express M.2 MiniCard
<b>Dimensions</b>	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm
<b>Weight</b>	1. Type 2230 : 2.8g 2. Type 1216: 1.3g
<b>Operating Voltage</b>	3.3v +/- 9%
<b>Temperature</b>	Operating: 14° to 158° F (-10° to 70° C) Non-operating: -40° to 176° F (-40° to 80° C)
<b>Humidity</b>	Operating: 10% to 90% (non-condensing) Non-operating: 5% to 95% (non-condensing)
<b>Altitude</b>	Operating: 0 to 10,000 ft (3,048 m) Non-operating: 0 to 50,000 ft (15,240 m)
<b>LED Activity</b>	LED Amber – Radio OFF; LED OFF – Radio ON
<b>Subtitle</b>	HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Wireless Technology
<b>Bluetooth Specification</b>	4.0/4.1/4.2/5.0/5.1/5.2/5.3/5.4 Compliant
<b>Frequency Band</b>	2402 to 2480 MHz



### Technical Specifications – Networking

<b>Number of Available Channels</b>	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
<b>Data Rates and Throughput</b>	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
<b>Transmit Power</b>	The Bluetooth component shall operate as a Class I Bluetooth device with a maximum transmit power of +15.5 dBm for BR and +13dBm for EDR.
<b>Power Consumption</b>	Peak (Tx): 330 mW Peak (Rx): 230 mW Selective Suspend: 17 mW
<b>Bluetooth Software Supported Link Topology</b>	1. Microsoft Windows Bluetooth Software 2. Linux/Chrome OS Bluetooth Software.
<b>Power Management</b>	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
<b>Certifications</b>	FCC (47 CFR) Part 15C/E, Section 15.247, 15.249, 15.407
<b>Bluetooth Profiles Supported</b>	ETSI 300 328, ETSI 301 893, ETSI 303 687 BT4.1-ESR 5/6/7 Compliance LE Link Layer Ping LE Dual Mode LE Link Layer LE Low Duty Cycle Directed Advertising LE L2CAP Connection Oriented Channels Train Nudging & Interlaced Scan BT4.2 ESR08 Compliance LE Secure Connection- Basic/Full LE Privacy 1.2 –Link Layer Privacy LE Privacy 1.2 –Extended Scanner Filter Policies LE Data Packet Length Extension FAX Profile (FAX) Basic Imaging Profile (BIP)2 Headset Profile (HSP) Hands Free Profile (HFP) Advanced Audio Distribution Profile (A2DP) BT5.2 ESR9/10 Compliance LE Advertisement Extensions Channel Selection Algo Limited High Duty Cycle Non-Connectable Advertising



### Technical Specifications – Networking

2Mbps LE  
LE Long Range  
BT5.3  
Host to Controller Encryption Key Control Enhancements  
Compliance to the latest Errata Section 12.3 of BT 5.3 specification

1. Wi-Fi 7 requires a Wi-Fi 7 router, sold separately, to function in the 6GHz band. Availability of public wireless access points limited. Wi-Fi 7 is backwards compatible with prior 802.11 specs. And available in countries where Wi-Fi 7 is supported. Wi-Fi 7 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.
2. Check latest software/driver release for updates on supported security features.
3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.
4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

#### HP 5G Sub-6 Cat 19

##### Technology/Operating bands

WCDMA/HSPA+ operating bands:

Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)  
Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)  
Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)  
Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)  
Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)

LTE FDD/TDD operating bands:

Band 1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)  
Band 2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)  
Band 3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)  
Band 4: 1710 to 1755 MHz (UL), 2110 to 2155 MHz (DL)  
Band 5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)  
Band 7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)  
Band 8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)  
Band 12: 699 to 716 MHz (UL), 729 to 746 MHz (DL)  
Band 13: 777 to 787 MHz (UL), 746 to 756 MHz (DL)  
Band 14: 788 to 798 MHz (UL), 758 to 768 MHz (DL)  
Band 17: 704 to 716 MHz (UL), 734 to 746 MHz (DL)  
Band 18: 815 to 830 MHz (UL), 860 to 875 MHz (DL)  
Band 19: 830 to 845 MHz (UL), 875 to 890 MHz (DL)  
Band 20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)  
Band 25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)  
Band 26: 814 to 849 MHz (UL), 859 to 894 MHz (DL)  
Band 28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)  
Band 29: 717 to 728 MHz (DL)  
Band 30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)  
Band 32: 1452 to 1496 MHz (DL)  
Band 34: 2010 to 2025 MHz (UL/DL)





### Technical Specifications – Networking

#### Wireless protocol standards

#### GPS GPS bands

Band 38: 2570 to 2620 MHz (UL/DL)  
 Band 39: 1880 to 1920 MHz (UL/DL)  
 Band 40: 2300 to 2400 MHz (UL/DL)  
 Band 41: 2496 to 2690 MHz (UL/DL)  
 Band 42: 3400 to 3600 MHz (UL/DL)  
 Band 43: 3400 to 3800 MHz (UL/DL)  
 Band 46: 5150 to 5925 MHz (DL)  
 Band 48: 3550 to 3700 MHz (UL/DL)  
 Band 66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)  
 Band 71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)  
 5GNR Sub 6GHz  
 n1: 1920 to 1980 MHz (UL), 2110 to 2170 MHz (DL)  
 n2: 1850 to 1910 MHz (UL), 1930 to 1990 MHz (DL)  
 n3: 1710 to 1785 MHz (UL), 1805 to 1880 MHz (DL)  
 n5: 824 to 849 MHz (UL), 869 to 894 MHz (DL)  
 n7: 2500 to 2570 MHz (UL), 2620 to 2690 MHz (DL)  
 n8: 880 to 915 MHz (UL), 925 to 960 MHz (DL)  
 n20: 832 to 862 MHz (UL), 791 to 821 MHz (DL)  
 n25: 1850 to 1915 MHz (UL), 1930 to 1995 MHz (DL)  
 n28: 703 to 748 MHz (UL), 758 to 803 MHz (DL)  
 n30: 2305 to 2315 MHz (UL) 2350 to 2360 MHz (DL)  
 n38: 2570 to 2620 MHz (UL/DL)  
 n40: 2300 to 2400 MHz (UL/DL)  
 n41: 2496 to 2690 MHz (UL/DL)  
 n48: 3550 to 3700 MHz (UL/DL)  
 n66: 1710 to 1800 MHz (UL), 2110 to 2200 MHz (DL)  
 n71: 663 to 698 MHz (UL), 617 to 652 MHz (DL)  
 n77: 3300 to 4200 MHz (UL/DL)  
 n78: 3300 to 3800 MHz (UL/DL)  
 n79: 4400 to 5000 MHz (UL/DL)  
 NR Sub6G rel15  
 200MHz 2 DLCA, 256 QAM  
 200MHz 2 ULCA, 256 QAM  
 15KHz/30KHz SCS for FDD/TDD  
 LTE Rel15  
 100MHz 5 DLCA, 256 QAM  
 40MHz 2 ULCA, 256 QAM  
 UMTS Rel8  
 GPS only support L1 C/A  
 GPS: L1 (1575.42MHz)  
 GLONASS: L1 (1602MHz)  
 BeidouB1(1561.098MHz)  
 Galileo E1 (1575.42)  
 QZSS(1575.42 MHz)



### Technical Specifications – Networking

<b>Maximum data rates</b>	Sub-6 SA Peak DL 4.67Gbps/UL 1.25Gbps Sub-6 NSA Peak DL 3.74Gbps/UL 835Mbps LTE Peak DL 1.6Gbps (CAT19)/UL 211Mbps (CAT18) UMTS/HSPA+ DL DC-HSPA+: 42 Mbps (CAT24)/UL 11.5 Mbps (CAT7)
<b>Maximum output power</b>	NR : 23 dBm in all band except (n30 = 22dBm & n48=21dBm & n77=25dBm & n41/n77/n78 = 26dBm) LTE: 23 dBm in all band except (B30 = 22dBm & B48=21dBm & B41=26dBm) UMTS: 23.5 dBm
<b>Maximum power consumption</b>	3500 mA (peak); 1674mA (average)
<b>Form Factor</b>	M.2, 3052-S3 Key B
<b>Weight</b>	8.7g
<b>Dimensions (Length x Width x Thickness)</b>	52 mm x 30 mm x 2.3 mm
<b>embedded eSIM</b>	Support

1. 5G module is optional and must be configured at the factory. Module designed for 5G NR NSA (non-standalone) networks as carriers deploy Evolved-Universal Terrestrial Radio Access New Radio Dual Connectivity (ENDC) with both 100Mhz of 5G NR and LTE channel bandwidth, using 256QAM 4x4 as defined by 3GPP. Module requires activation and separately purchased service contract. Check with service provider for coverage and availability in your area. Data connection, upload and download speeds will vary due to network, location, environment, network conditions, and other factors. Backwards compatible to 4G LTE and 3G HSPA technologies. 5G module planned to be available in select platforms and select countries, where carrier supported.

### Qualcomm 9205

<b>Technology/Operating bands</b>	FDD LTE: 2100 (Band 1), 1900 (Band 2), 1800 (Band 3), 1700/2100 (Band 4), 850 (Band 5), 900 (Band 8), 700 (Band 12 lower), 700 (Band 13 upper), 700 (Band 14 upper), 850 (Band 18 lower), 850 (Band 19 upper), 800 (Band 20), 1900 (Band 25), 850 (Band 26), 800 (Band 27), 700 (Band 28), 1700/2100 (Band 66), 700 (band 85) MHz. GSM/GPRS/EGPRS: 850, 900, 1800, 1900MHz.
<b>Wireless protocol standards</b>	l 3GPP TS 51.010-1 V10.5.0: Mobile Station (MS) conformance specification; Part 1: Conformance specification l 3GPP TS 36.521-1 V14.3.0: User Equipment (UE) conformance specification; Radio transmission and reception; Part 1: Conformance testing l 3GPP TS 21.111 V10.0.0: USIM and IC card requirements l 3GPP TS 51.011 V4.15.0: Specification of the Subscriber Identity



### Technical Specifications – Networking

	Module -Mobile Equipment (SIM-ME) interface
	l 3GPP TS 31.102 V10.11.0: Characteristics of the Universal Subscriber Identity Module (USIM) application
	l 3GPP TS 31.11 V10.16.0: Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)
	l 3GPP TS 36.124 V10.3.0: Electro Magnetic Compatibility (EMC) requirements for mobile terminals and ancillary equipment
	l 3GPP TS 27.007 V10.0.8: AT command set for User Equipment (UE)
	l 3GPP TS 27.005 V10.0.1: Use of Data Terminal Equipment - Data Circuit terminating Equipment (DTE - DCE) interface for Short Message Service (SMS) and Cell Broadcast Service (CBS)
<b>GPS</b>	Standalone GPS/Beidou/Glonass, A-GPS(XTRA)
<b>GPS bands</b>	1575.42 MHz ± 1.023 MHz, GLONASS 1596-1607MHz, Beidou 1561.098 MHz
<b>Maximum data rates</b>	LTE FDD: 375 Kbps (Download), 1119 Kbps (Upload) GSM: - GPRS: 107 Kbps (Download), 85.6 Kbps (Upload) - EGPRS: 296 Kbps (Download), 236.8 Kbps (Upload)
<b>Maximum output power</b>	LTE: 21.5 dBm in all band GSM:34dBm
<b>Maximum power consumption</b>	LTE: 147 mA(peak), 18 mA(average)
<b>Form Factor</b>	M.2
<b>Weight</b>	4 g
<b>Dimensions (Length x Width x Thickness)</b>	22 x 42 x 2.3 mm
<b>embedded eSIM</b>	Support
<b>NFC NXP NPC300</b>	
<b>Dimensions (L x W x H)</b>	17 x 10 x 2.0 mm
<b>Chipset</b>	NPC300
<b>System interface</b>	I2C
<b>NFC RF standards</b>	ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 ISO/IEC 18092 ECMA-340 NFCIP-1 Target and Initiator ECMA-320 NFCIP-2
<b>NFC Forum Support Reader (PCD-VCD) Mode(1)</b>	Tag Type 1, Type 2, Type3 and Type 4, NFCIP-1 and NFCIP-2 ISO/IEC 14443 A ISO/IEC 14443 B ISO/IEC 15693 MIFARE 1K MIFARE 4K



### Technical Specifications – Networking

<b>Card Emulation (PICC-VICC Mode(1))</b>	MIFARE DESFire FeliCa Jewel and Topaz cards ISO/IEC 14443 A ISO/IEC 14443 B and B' MIFARE FeliCa
<b>Frequency</b>	13.56 MHz
<b>NFC Modes Supported</b>	Reader/Writer, Peer-to-Peer
<b>Raw RF Data Rates</b>	106, 212, 424, 848 kbps
<b>Operating temperature</b>	Operating: 0 °C to 70 °C (32 °F to 158 °F)
<b>Storage temperature</b>	Storage: -20 °C to 125 °C (-4 °F to 257 °F)
<b>Humidity</b>	10-90% operating 5-95% non-operating
<b>Supply Operating voltage</b>	4.35 to 5.25 Volts
<b>I/O Voltage</b>	1.8V or 3.3V
<b>Power Consumption (Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)</b>	(Booster enable, VBAT= 3.3V, VCC_BOOST = 5V)
<b>Mode</b>	Power Consumption, Typical
<b>Polling</b>	7.3 mA
<b>Detected Test Tag Type 1</b>	Total 283.8 mA Net Module 236.8 mA
<b>Detected Test Tag Type 2</b>	Total 288.8 mA Net Module 241.8 mA
<b>Detected Test Tag Type 3</b>	Total 287.7 mA Net Module 240.7 mA
<b>Detected Test Tag Type 4</b>	Total 282.3 mA Net Module 235.3 mA
<b>Antenna</b>	Antenna connector, 0.5mm pitch, 7 connector FPC. Antenna matching is external to module.
<b>Intel® I226-LM 2.5 Gigabit Network Connection LOM (vPro)</b>	
<b>Connector</b>	RJ-45
<b>System Interface</b>	PCI(Intel proprietary) + SMBus
<b>Data rates supported</b>	1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14) 2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30) 3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40)



### Technical Specifications – Networking

		<p>4. 2.5 Gbit/s operation( 2.5GBASE-T; IEEE 802.3bz Clause 126)</p> <p>5. Auto-Negotiation (Automatic Speed Selection)</p> <p>Full Duplex Operation at all Speeds, Half Duplex operation at 10 &amp; 100 Mbit/s</p>
	<p><b>IEEE Compliance</b></p>	<p>IEEE 802.1p QoS (Quality of Service) Support</p> <p>IEEE 802.1q VLAN support</p> <p>IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)</p> <p>IEEE 802.3az EEE (Energy Efficient Ethernet)</p> <p>IEEE 802.3i 10BASE-T</p> <p>IEEE 802.3u 100BASE-TX</p> <p>IEEE 802.3ab 1000BAE-T</p> <p>IEEE 802.3bz 2.5GBASE-T</p>
	<p><b>Performance</b></p>	<p>TCP/IP/UDP Checksum Offload (configurable)</p> <p>Protocol Offload (ARP &amp; NS)</p> <p>Large send offload and Giant send offload</p> <p>Receiving Side Scaling(Hash Mode Only)</p> <p>Jumbo Frame 9K</p>
	<p><b>Power consumption</b></p>	<p>Cable Disconnection: 25mW</p> <p>100Mbps Full Run: 450mW</p> <p>1000Mbp Full Run: 1000mW</p> <p>2500Mbp Full Run: 4500mW</p> <p>WoL Enable(S3/S4/S5): 50mW</p> <p>WoL Disable(S3/S4/S5): 25mW</p>
	<p><b>Power Management</b></p>	<p>ACPI compliant – multiple power modes</p> <p>Situation-sensitive features reduce power consumption</p> <p>Advanced link down power saving for reducing link down power consumption</p>
	<p><b>Management Interface IT Manageability</b></p>	<p>Auto MDI/MDIX Crossover cable detection</p> <p>Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)</p> <p>PXE 2.1 Remote Boot</p> <p>Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))</p> <p>Comprehensive diagnostic and configuration software suite</p> <p>Virtual Cable Doctor for Ethernet cable status</p>
	<p><b>Security &amp; Manageability</b></p>	<p>Intel® vPro™ support with appropriate Intel® chipset components</p>
<p><b>Intel® I226V 2.5 Gigabit Network Connection LOM (non-vPro)</b></p>	<p><b>Connector System Interface</b></p>	<p>RJ-45</p> <p>PCI(Intel proprietary) + SMBus</p>



### Technical Specifications – Networking

#### Data rates supported

1. 10 Mbit/s operation (10BASE-T; IEEE 802.3i; IEEE 802.3 clauses 13-14)
2. 100 Mbit/s operation (100BASE-TX; IEEE 802.3u; IEEE 802.3 clauses 21-30)
3. 1000 Mbit/s operation (1000BASE-T; IEEE 802.3ab; IEEE 802.3 clauses 40)
4. 2.5 Gbit/s operation (2.5GBASE-T; IEEE 802.3bz Clause 126)
5. Auto-Negotiation (Automatic Speed Selection)

Full Duplex Operation at all Speeds, Half Duplex operation at 10& 100 Mbit/s

#### IEEE Compliance

IEEE 802.1p QoS (Quality of Service) Support

IEEE 802.1q VLAN support

IEEE 802.3x Flow Control (IEEE 802.3 clauses 31-32; configurable)

IEEE 802.3az EEE (Energy Efficient Ethernet)

IEEE 802.3i 10BASE-T

IEEE 802.3u 100BASE-TX

IEEE 802.3ab 1000BAE-T

IEEE 802.3bz 2.5GBASE-T

#### Performance

TCP/IP/UDP Checksum Offload (configurable)

Protocol Offload (ARP & NS)

Large send offload and Giant send offload

Receiving Side Scaling (Hash Mode Only)

Jumbo Frame 9K

#### Power consumption

Cable Disconnection: 25mW

100Mbps Full Run: 450mW

1000Mbps Full Run: 1000mW

2500Mbps Full Run: 4500mW

WoL Enable (S3/S4/S5): 50mW

WoL Disable (S3/S4/S5): 25mW

#### Power

#### Management

ACPI compliant – multiple power modes

Situation-sensitive features reduce power consumption

Advanced link down power saving for reducing link down power consumption

#### Management Interface

#### IT Manageability

Auto MDI/MDIX Crossover cable detection

Wake-on-LAN from modern standby or sleep state (Magic Packet and Microsoft Wake-Up Frame); Wake-on-LAN from off (Magic Packet only)

PXE 2.1 Remote Boot

Statistics Gathering (SNMP MIB II, Ethernet-like MIB, Ethernet MIB (802.3x, clause 30))

Comprehensive diagnostic and configuration software suite

Virtual Cable Doctor for Ethernet cable status



Technical Specifications – Networking

Security & Manageability

Intel® non-vPro™ support with appropriate Intel® chipset components



### Technical Specifications – Power

#### POWER

Power supply availability may vary by country.

**HP 200W Slim 4.5 mm PFC  
Right Angle Smart (3-pin) AC  
Power Adapter Eris+**

<b>Dimensions</b>	6.496 x 3.11 x 1.0 in (16.5x7.9x2.54cm)
<b>Weight</b>	530g(+/-10g) (Not including power cord. Power cord varies by country.)
<b>Input Voltage</b>	100-240Vac
<b>Input Efficiency</b>	88 % at 115 Vac and 89 % at 230Vac
<b>Input frequency range</b>	47-63 Hz
<b>Input AC current</b>	Max. 3.0 A at 90 Vac
<b>Output</b>	
<b>Output power</b>	200W
<b>DC output</b>	19.5V
<b>Hold-up time</b>	100% load 5ms at 115 Vac input
<b>Output Over Current</b>	< 21.0A
<b>Protection</b>	
<b>Connector</b>	C14
<b>Connector</b>	4.5mm Barrel Type
<b>Environmental Design</b>	
<b>Operating temperature</b>	32oF to 95oF (0oto 35oC)
<b>Non-operating (storage) temperature</b>	-4oF to 185oF (-20oto 85oC)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC), NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC

**HP 280W Standard 4.5 mm  
Right Angle Smart (3-pin) AC  
Power Adapter Bowser+**

<b>Dimensions</b>	7.087 x 3.465 x 1.0 in (18.0x8.8x2.54cm)
<b>Weight</b>	730g(+/-10g) (Not including power cord. Power cord varies by country.)





### Technical Specifications – Power

<b>Input Voltage</b>	100-240Vac
<b>Input Efficiency</b>	89 % at 115Vac/230Vac
<b>Input frequency range</b>	47-63 Hz
<b>Input AC current</b>	Max. 4.0 A at 90 Vac
<b>Output</b>	
<b>Output power</b>	280W
<b>DC output</b>	20.0V
<b>Hold-up time</b>	100% load 10ms at 115 Vac input
<b>Output Over Current Protection</b>	< 28.0A
<b>Connector</b>	C14
<b>Connector</b>	4.5mm Barrel Type
<b>Environmental Design</b>	
<b>Operating temperature</b>	32oF to 95oF (0oto 35oC)
<b>Non-operating (storage) temperature</b>	-4oF to 185oF (-20oto 85oC)
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC

### HP 330W Standard 4.5 mm PFC Straight Smart (3-pin) AC Power Adapter Luigi

<b>Dimensions</b>	7.87 x 3.54 x 1.0 in (20.0x9.0x2.54cm)
<b>Weight</b>	770g(+/-10g) max (Not including power cord. Power cord varies by country.)
<b>Input Voltage</b>	100-240Vac
<b>Input Efficiency</b>	89 % at 115Vac/230Vac
<b>Input frequency range</b>	47-63 Hz
<b>Input AC current</b>	Max. 4.2 A at 90 Vac
<b>Output</b>	330W
<b>Output power</b>	20.0V
<b>DC output</b>	
<b>Hold-up time</b>	100% load 10ms at 115 Vac input
<b>Output Over Current Protection</b>	< 25.0A
<b>Connector</b>	C14



### Technical Specifications – Power

<b>Connector</b>	4.5mm Barrel Type
<b>Environmental Design</b>	
<b>Operating temperature</b>	32oF to 95oF (0oto 35oC)
<b>Non-operating (storage) temperature</b>	-4oF to 185oF (-20oto 85oC)
<b>Non-operating (storage) temperature</b>	
<b>Altitude</b>	0 to 16,400 ft (0 to 5000m)
<b>Humidity</b>	20% to 95%
<b>Storage Humidity</b>	10% to 95%
<b>EMI and Safety Certifications</b>	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1, IEC 62368-1:2014 and IEC62368-1 : 2018, EN62368-1:2020+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC, CU(EAC), KCC(Safety+EMC), NOM-001 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia RCM, BIS, BSMI, UAE, UKCA DoC

### GE 99Whr Long Life Polymer Fast Charge 8 cell Battery

<b>Weight</b>	0.41kg +/- 10g(0.90 lb)
<b>Cells/Type</b>	8 cell Lithium-Ion Polymer cell /574269
<b>Energy</b>	
<b>Voltage</b>	15.56V
<b>Amp-hour capacity</b>	6.37Ah
<b>Watt-hour capacity</b>	99.1Wh
<b>Temperature</b>	
<b>Operating (Charging)</b>	0° to 45° C (32° to 113° F)
<b>Operating (Discharging)</b>	-10° to 65° C (14° to 149° F)
<b>Fuel Gauge LED</b>	
<b>Warranty</b>	
<b>Optional Travel Battery Available</b>	



Technical Specifications – Audio

<b>AUDIO</b>	
<b>HD Stereo Codec</b>	Realtek ALC3315
<b>Audio I/O Ports</b>	Support 3.5mm Headset : CTIA only and Headphone-out
<b>Internal Speaker Amplifier</b>	Texas Instruments digital input Class-D smart audio amplifiers
<b>Multi-streaming Capable</b>	Playback multi-streaming can be enabled in the audio control panel to allow independent audio. Following MSFT Behaviour
<b>Sampling</b>	DAC:48kHz 16bits~24bits ADC:44.1k~48kHz 16bits~24bits
<b>Analog Audio</b>	Support 3.5mm Headset : CTIA only and Headphone-out
<b>Internal Speaker</b>	Yes

Technical Specifications – Fingerprint Reader

FINGERPRINT READER

Sensor vendor	Synaptics FS7614
Sensor type	Capacitive
DPI resolution	363 DPI
Scan area	104 x 86 pixels
False Rejection Rate	<3%
False Acceptance Rate	< 0.001%
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	0°~60°C
Current Consumption Image	100mA max
Low Latency Wait For Finger	260uA
Capture Rate	Image transmitter output frequency 9.6MHz
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	363 dpi / 7.4x6mm sensor area
Footnotes	

## Technical Specifications – Environmental

## ENVIRONMENTAL DATA

## Eco-Label Certifications &amp; declarations

This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:

- IT ECO declaration
- US ENERGY STAR®
- US Federal Energy Management Program (FEMP)
- EPEAT® Gold registered in the United States. See <http://www.epeat.net> for registration status in your country.
- TCO Certified
- China Energy Conservation Program (CECP)
- China State Environmental Protection Administration (SEPA)
- Taiwan Green Mark
- Korea Eco-label
- Japan PC Green label\*
- [Product Carbon Footprint](#)
- At least 30% ocean bound plastic in the speaker<sup>1</sup>
- At least 30% post-consumer recycled plastic<sup>2</sup>
- At least 85% recycled metal<sup>3</sup>
- Low Halogen<sup>4</sup>
- 100% of HP paper-based packaging is from recycled or certified sustainable sources<sup>5</sup>
- Bulk packaging available

## Sustainable Impact Specifications

## System Configuration

The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a “Typically Configured Notebook”.

Energy Consumption  
(in accordance with US ENERGY STAR® test method)

	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
Normal Operation (Short idle)	8.01 W	7.84 W	8.16 W
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	1.79 W	1.82 W	1.87 W
Off	0.40 W	0.40 W	0.39 W

**NOTE:**

Energy efficiency data listed is for an ENERGY STAR® compliant product if offered within the model family. HP computers marked with the ENERGY STAR® Logo are compliant with the applicable U.S. Environmental Protection Agency (EPA) ENERGY STAR® specifications for computers. If a model family does not offer ENERGY STAR® compliant configurations, then energy efficiency data listed is for a typically configured PC featuring a hard disk drive, a high efficiency power supply, and a Microsoft Windows® operating system.

## Heat Dissipation\*

115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz
--------------	--------------	--------------



### Technical Specifications – Environmental

Normal Operation (Short idle)	27 BTU/hr	27 BTU/hr	28 BTU/hr
Normal Operation (Long idle)	N/A	N/A	N/A
Sleep	6.1 BTU/hr	6 BTU/hr	6.4 BTU/hr
Off	1.4 BTU/hr	1 BTU/hr	1.3 BTU/hr

**\*NOTE:** Heat dissipation is calculated based on the measured watts, assuming the service level is attained for one hour.

#### Declared Noise Emissions (in accordance with ISO 7779 and ISO 9296)

	Sound Power ( $L_{Wad}$ , bels)	Sound Pressure ( $L_{pAm}$ , decibels)
Typically Configured – Idle	2.6	14.6
Fixed Disk – Random writes	3.5	24.0
Optical Drive – Sequential reads	5.0	35.8

#### Longevity and Upgrading

This product can be upgraded, possibly extending its useful life by several years. Upgradeable features and/or components contained in the

Spare parts are available throughout the warranty period and or for up to “5” years after the end of production.

#### Additional Information

- This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive - 2011/65/EC.
- This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.
- This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).
- This product is in compliance with the IEEE 1680 (EPEAT) standard at the Gold level, see [www.epeat.net](http://www.epeat.net)
- Plastics parts weighing over 25 grams used in the product are marked per ISO11469 and ISO1043.
- This product is 98.3% recycle-able when properly disposed of at end of life.

#### Packaging Materials

<b>External:</b>	PAPER/Corrugated	39 g
	PAPER/Molded Pulp	240 g
	PAPER/Paper	31 g

The plastic packaging material contains at least 0.0% recycled content.

The corrugated paper packaging materials contains at least 57.9% recycled content.

#### RoHS Compliance

HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directive to our



### Technical Specifications – Environmental

products worldwide through the HP GSE. HP has contributed to the development of related legislation in Europe, as well as China, India, and Vietnam.

We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.

We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.

To obtain a copy of the HP RoHS Compliance Statement, see [HP RoHS position statement](#).

### Material Usage

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at

<https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c05998906>):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants – may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Bis(2-Ethylhexyl) phthalate (DEHP)
- Benzyl butyl phthalate (BBP)
- Dibutyl phthalate (DBP)
- Diisobutyl phthalate (DIBP)
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBEBs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTTO)



### Technical Specifications – Environmental

#### Packaging Usage

HP follows these guidelines to decrease the environmental impact of product packaging:

- Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.
- Eliminate the use of ozone-depleting substances (ODS) in packaging materials.
- Design packaging materials for ease of disassembly.
- Maximize the use of post-consumer recycled content materials in packaging materials.
- Use readily recyclable packaging materials such as paper and corrugated materials.
- Reduce size and weight of packages to improve transportation fuel efficiency.
- Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.

#### End-of-life Management and Recycling

HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to:

<https://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c05403198> or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.

The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: [HP Product Disassembly Instruction Website](#). These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.

#### HP Inc. Corporate Environmental Information

For more information about HP's commitment to the environment:

- Sustainable Impact Report
  - <https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c06040843>
- Eco-label certifications
  - [https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters\\_documents\\_reports=-document\\_type-type\\_energy\\_star,type\\_epeat,type\\_tcoISO](https://www.hp.com/us-en/sustainable-impact/document-reports.html#filters_documents_reports=-document_type-type_energy_star,type_epeat,type_tcoISO)
- ISO 14001 certificates
  - <https://h20195.www2.hp.com/v2/GetDocument.aspx?docname=c04777932>

#### Footnotes

1. Percentage of ocean-bound plastic contained in each component varies by product. Ocean Bound plastic is expressed as a percentage of the total weight plastic. Ocean Bound plastic is based on the definition set by the UL2809 standard.
2. Recycled plastic is expressed as a percentage of the total weight plastic. Post-consumer recycled is based on the definition set in the EPEAT standard for computers, IEEE 1680.1-2018 standard.
3. Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
4. External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.
5. HP paper and fiber-based packaging for PCs, displays, home and office print, and supplies is reported by suppliers as recycled or certified, with a minimum of 97% by volume verified by HP. Packaging is the box that comes with the product and all paper-based materials inside the box.





---

### Technical Specifications – Environmental

Packaging for personal systems accessories and spare parts is not included. Plastic cushions are made from >90% recycled plastic.

---



Options and Accessories (sold separately and availability may vary by country)

Type	Description	Part#
<b>Docking</b>	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4AA
	HP Thunderbolt 280W G4 Dock w/Combo Cable	4J0G4ET
	HP Thunderbolt 280W TAA G4 Dock w/Combo Cable	4J0J9AA
<b>Input/Output</b>	HP USB-C to USB-C 100W Cable	5AR72AA
<b>Keyboard/Mouse</b>	HP 320K Wired Keyboard	9SR37AA
	HP 975 USB+BT Dual-Mode Wireless Keyboard	3Z726AA
	HP 455 Programmable Wireless Keyboard	4R177AA
	HP 455 Programmable USB Wireless Keyboard (Bulk Qty.12)	4R177A6
	HP 965 BLK Ergonomic Wireless Keyboard	7E756AA
	HP 475 Dual-Mode Wireless Keyboard	7N7B9AA
	HP 475 Dual-Mode Wireless Keyboard	7N7B9UT
	HP 405 Multi-Device Backlit Wired Keyboard	7N7C1AA
	HP 405 Multi-Device Backlit Wired Keyboard	7N7C1UT
	HP 435 Programmable Bluetooth Wireless Keypad	7N7C3AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
	HP 655 Wireless Keyboard and Mouse Combo	4R009AA
	HP 655 Wireless Keyboard and Mouse Combo (Blk Qty.10)	4R009A6
	HP Wired 320M Mouse	9VA80AA
	HP Multi-Device 635 Black Wireless Mouse	1D0K2AA
	HP Creator 935 Black Wireless Mouse	1D0K8AA
	HP 235 Slim Wireless Mouse	4E407AA
	HP 235 Slim Wireless Mouse	4E407UT
	HP 435 Multi-Device Wireless Mouse	3B4Q5UT
	HP 715 Rechargeable Multi-Device Bluetooth Mouse	6E6F0AA
	HP 925 Ergonomic Vertical Wireless Mouse	6H1A5AA
	HP 695 Qi-Charging Wireless Mouse	8F1Y4AA



Options and Accessories (sold separately and availability may vary by country)

	HP Tilt Ergonomic Mouse 725M	BH0Z5AA
Hub	HP USB-C to USB-A Hub	Z6A00AA
	HP Portable USB-C Hub	B8SU8UT
	HP Portable USB-C Hub	B8SV8AA
Audio	HP USB G2 Stereo Headset	428H5AA
	HP USB G2 Stereo Headset	428K6AA
	HP USB G2 Stereo Headset	428K6PT
Power	HP 330W Smart AC Adapter	BF7A6AA
	HP 330W Smart AC Adapter	BF7C7AA
Security	HP Nano Keyed Cable Lock	1AJ39AA
	HP Nano Master Keyed Cable Lock	1AJ40AA
	HP Sure Key Cable Lock	6UW42AA
	HP Nano Combination Cable Lock	63B28AA
	HP Essential Nano Combination Cable Lock	63B31AA



Date of change	Version History		Description of change
June 2, 2025	From v1 to v2	Changed	Format
June 9, 2025	From v2 to v3	Changed	ENVIRONMENTAL DATA section

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Core, Thunderbolt and Intel vPro are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. DisplayPort™ and the DisplayPort™ logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. USB Type-C® and USB-C® are trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.